Product data sheet
Characteristics

8903SMA91V02
Contactor, Type S, combination lighting, mechanically held, 30A, 3 pole, breaker, 110/120 VAC 50/60 Hz coil, NEMA 12



Main

Product	Combination mechanically held lighting contactor
Type	S

Complementary

Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Current Rating	30 A
Number of Poles	3P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Options	None
Disconnector device type	Thermal magnetic circuit breaker, 30 A 600 V
Electrical Connection	Lugs
Height	12.8 in (324 mm)
Depth	8.5 in (217 mm)
Width	6.4 in (162 mm)

Environment

Enclosure Type	NEMA 12/3R painted sheet steel surface none
Product Certifications	UL listed file E16151 CCN NRNT

Ordering and shipping details

Category	21324 - 8903 S (NOT S*C) MECH.
Discount Schedule	CP1
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.8 in (32.4 cm)
Package 1 Width	6.4 in (16.2 cm)
Package 1 Length	8.5 in (21.7 cm)
Package 1 Weight	28.949 lb(US) (13.131 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

EU RoHS Directive	Under investigation
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months