Product datasheet
Characteristics

8940XSG4200V06L9Y1Y35

Main

Product name	Well-Guard Control
Device short name	Class 8940 type X
Device application	Pumping

Complementary

Control circuit	Common control circuit
[Uc] control circuit voltage	440 V AC 50 Hz 480 V AC 60 Hz
Line Rated Current	270 A
Number of poles	3
Motor power hp	200 hp at 480 V AC for 3 phases
Permissible voltage	600 V at AC
Control type	(HAND-OFF-AUTO) selector switch (START) push-button
Disconnector device type	Associated circuit breaker
Circuit breaker CT rating	400 A
Circuit breaker type	LLL
Thermal overload type	Motor Logic solid state class 10/20
Protection type	Overload Phase unbalance Phase loss
Device mounting	Surface
Electrical connection	Screw terminal
NEMA size	5
Height	1892 mm
Width	23.5 in (597 mm)
Depth	446 mm

Environment

NEMA degree of protection	NEMA 3R
enclosure type	Weatherproof enclosure indoor/outdoor
product certifications	NEMA UL listed

Contractual warranty

Warranty period	18 months

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.