Product data sheet
Characteristics

2510MBG2X1
Manual Starter - NEMA 1 - Buttons - 3P - Size M0 -No Ind-NO Aux Contact 600VAC

Product availability : Stock - Normally stocked in distribution facility

Price* : 485.21 USD



Main

Product or component type	Manual Starter
Range of product	M
NEMA size	M-0

Complementary

Control type	Push-button
Local signalling	No indicator
Motor power hp	3 hp at 200...230 V AC 3 phases 5 hp at 380...575 V AC 3 phases
System Voltage	600 V AC
Poles description	3P
Motor starter type	Non reversing
Electrical connection	Pressure wire clamp
Thermal overload type	Melting alloy
Number of thermal units required	3
AWG gauge	AWG 14...AWG 8 (copper)
Auxiliary contact composition	1 NO
Height	8.63 in
Width	5 in
Depth	4.13 in

Environment

Product certifications	UL listed file E42243 CCN NLRV CSA LR60905 class 3211 05
NEMA degree of protection	NEMA 1 painted sheet steel

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ordering and shipping details

Category	21103 - 2510,2511,2512 M,T
Discount Schedule	CP1
GTIN	00785901764175
Nbr. of units in pkg.	1
Package weight(Lbs)	4.5
Returnability	N
Country of origin	MX

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will not be compliant Will not be compliant
REACh	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months