Product data sheet

Specifications



NEMA Motor Starter and contactor, Type S, auxiliary contact, 1 NO/1 NC isolated contact, external, field convertible

9999SX8

Product availability: Stock - Normally stocked in distribution facility

Main

Product Range	Type S
Component type	Auxiliary Contact Module
Used with	contactor starter

Complementary

NEMA size	3 4 00 1 6 2 5 7 0
Auxiliary contact composition	1 NO + 1 NC
[Uc] control circuit voltage	<= 600 V AC 50/60 Hz
Rated breaking capacity	6 A 120 V AC inductive control circuit UL 508 3 A 240 V AC inductive control circuit UL 508 1.2 A 600 V AC inductive control circuit UL 508 1.5 A 480 V AC inductive control circuit UL 508 10 A <= 600 V AC resistive control circuit UL 508
Height	1.5 in (38.1 mm)
Width	3 in (76.2 mm)
Depth	4.5 in (114.3 mm)
Product Weight	0.31 lb(US) (0.14 kg)

Environment

Product Certifications	CSA UL Recognized UL Listed

Ordering and shipping details

Category	US10CP121761
Discount Schedule	0CP1
GTIN	785901733539
Returnability	Yes
Country of origin	MX

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.500 in (3.810 cm)
Package 1 Width	3.000 in (7.620 cm)
Package 1 Length	4.700 in (11.938 cm)
Package weight(Lbs)	4.960 oz (140.614 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	6.000 in (15.240 cm)
Package 2 Width	6.800 in (17.272 cm)
Package 2 Length	8.000 in (20.320 cm)
Package 2 Weight	3.0005 lb(US) (1.361 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Circularity Profile	**No need of specific recycling operations**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**